


PIN NO.	1	2	3	4	5	6	7
Symbol	FG	VSS	VDD	VO	WR	RD	OE
PIN NO.	8	9	10-17	18	19	20	21
Symbol	C/D	RET	DB0-DB7	FS	VEE	LED+	LED-
PIN NO.	22	23	24	25	26-33	34	35
Symbol	LED-	LED+	VEE	FS	DB7-DB0	RET	NC
PIN NO.	36	37	38	39	40	41	42
Symbol	C/D	OE	RD	WR	VO	VDD	VSS
PIN NO.	43						
Symbol	FG						



NOTE: 1. Pin No.18 FS: FONT SELECT  
FS=L8X8 Character Font

- NOTE:
- 1.DISPLAY TYPE : STN
  - 2.VIEWING DIRECTION: 12:00
  - 3.POLARIZER MODE: TRANSMISSIVE/NEGATIVE
  - 4.DRIVE METHOD:1/128DUTY,1/12BIAS
  - 5.OPERATING VOLTAGE:18.5V(REFERENCE)
  - 6.OPERATING TEMP:-20°C~+70°C
  - 7.STORAGE TEMP:-30°C~+80°C
  - 8.CONNECTION: ZEBRA
  - 9.BACKLIGHT:WHITE,5.0V,120mA,8 Dices
  - 10.LCD CONTROLLER:T6963C
  - 11.POWER SUPPLY FOR LOGIC:5.0V



HTDISPLAY CO., LTD.

TOLERANCE	>0~6 ±0.10	DESIGN	JHG	20060923	STANDARD	REV. : A	SCALE : -
	>6~80 ±0.20	CHECKED			TECHNOLOGY	PROJECTION:	UNIT : MM
	>80~240 ±0.30	APPROVED			Q. A		SHEET : 1/1
	>240~400 ±0.50						
	// ±0.10						

DRAWING No. : H624012802C-61C2L-VE  
DRAWING TITLE: LCM Drawing  
FILE NO. : 8